

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 602 560 A1

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **93119930.1**(51) Int. Cl.⁵: **B01D 63/08, B01D 69/10,
B01D 65/00**(22) Date of filing: **10.12.93**

(30) Priority: **16.12.92 JP 334791/92**
21.01.93 JP 8000/93
16.07.93 JP 176317/93
16.07.93 JP 176318/93

(43) Date of publication of application:
22.06.94 Bulletin 94/25

(84) Designated Contracting States:
BE CH DE ES FR GB IT LI NL SE

(71) Applicant: **KUBOTA CORPORATION**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)

(72) Inventor: **Shimizu, Kenji, c/o Kubota Co.**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)
Inventor: **Ishida, Hiroshi, c/o Kubota Co.**


2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)
Inventor: **Yamada, Yutaka, c/o Kubota Co.**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)
Inventor: **Izumi, Kiyoshi, c/o Kubota Co.**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)
Inventor: **Moro, Masashi, c/o Kubota Co.**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)
Inventor: **Soeda, Yuji, c/o Kubota Co.**
2-47, Shikitsuhigashi 1-chome
Naniwa-ku, Osaka(JP)

(74) Representative: **Le Vrang, Klaus**
Fliederstrasse 1
D-85139 Wettstetten (DE)

(54) **Filtration membrane cartridge.**

(57) A pair of filtering membranes 52 are solidly bonded to a membrane-supporting plate 51 by fusibly bonding each of the filtering membranes 52 to the resin membrane-supporting plate 51. A main fusible domain is formed along peripheral edges of each of the filtering membrane 52. In addition, a plurality of subordinate fusible domains are intermittently formed in plural locations on one side or on both sides of the main fusible domain. By virtue of the above structure, bonding strength is secured by the main fusible domain, and yet, bonding strength is reinforced by locally provided subordinate fusible domains. A channel is formed in the membrane-supporting plate 51 so that permeated liquid can swiftly flow through the filtering system. In addition, a plurality of projections 53 are formed on peripheral edges of a filtration membrane cartridge 5 facing inner surface of each gutter formed inside of each slit plate by way of causing respective projections 53 to slidably come into contact with the inner surface of the gutter. This in turn effectively minimizes frictional force between the filtration membrane car-

tridge 5 and the gutter to facilitate operator to easily insert and remove the filtration membrane cartridge 5 into and from the gutter of the slit plate.

FIG.5**EP 0 602 560 A1**

FIELD OF THE INVENTION

The present invention relates to a filtration membrane cartridge used for solid liquid separation. More particularly, the invention relates to a filtration membrane cartridge sharing most essential part of a membrane separation device.

BACKGROUND OF THE INVENTION

As shown in Fig. 1, a typical conventional membrane separation device is provided with a filtering membrane unit 3 which is disposed by way of being submerged in raw liquid pooled in a raw liquid processing tank. The conventional filtering membrane unit 3 incorporates a plurality of filtration membrane cartridges 5 inside of an upper casing 4 by vertically aligning them in parallel with each other at prederemined intervals. In addition, a gas supply unit 7 is disposed inside of a lower casing 6 in order to feed gas such as oxygen, air, or nitrogen gas, to raw liquid in accordance with objective uses. Each of the filtration membrane cartridges 5 stored in the filtering membrane unit 3 is internally provided with a permeated-liquid passage connected to a routed tube 9 of a suction tube 8 for sucking permeated liquid, where an end of the suction tube 8 is linked with a suction pump 10.

While operating the conventional membrane separation device 1, the suction pump 10 generates negative pressure against all the filtration membrane cartridges 5 stored in the filtering membrane unit 3 in order that permeated liquid can properly be sucked. On the other hand, gas such as oxygen or air (designated by arrowed mark A) is supplied to the gas supply unit 7 from an external source to enable the gas supply unit 7 to jet out bubble flow into space between adjoining filtration membrane cartridges 5 in the upward direction from the bottom of the filtering-membrane unit 3. Upwardly flowing bubble generates aerial lifting action to cause tangential flow along the membrane surface, said tangential flow sweeping away deposit on the membrane surface.

Conventionally, each filtration membrane cartridge 5 stored in the membrane separation device 1 is inserted in a gutter provided inside of each slit plate vertically set in the upper casing 4. However, since each filtration membrane cartridge 5 and the inner surface of each gutter remain in contact with each other via substantial surface area, friction is generated between both surfaces to check operator to smoothly insert and take out each of the cartridges 5 into and from the gutter.

Normally, any conventional filtration membrane cartridge 5 is based on the structure in which an organic filtering membrane is secured onto the surface of a plane rectangular membrane-support-

ing plate by bonding peripheral domains of the organic filtering membrane to the membrane-supporting plate. On the other hand, when securing the filtering membrane to the membrane-supporting plate with adhesive agent, adhesive strength is variable according to strength, durability, and chemical resistance property of the selected adhesive agent, and therefore, filtering membrane may incidentally be stripped off from the membrane-supporting plate.

DISCLOSURE OF THE INVENTION

Therefore, the object of the invention is to fully solve those problems described above by providing an improved filtration membrane cartridge that can readily be inserted into and removed from a filtering membrane unit and prevent filtering membranes from being stripped off from the membrane-supporting plates.

To achieve the above object, the improved filtration membrane cartridge according to the invention disposes each filtering membrane on both surfaces of a membrane-supporting plate made of resin and secures edges of the filtering membranes to the membrane-supporting plate by way of fusing both of them or either of them for adhesion therebetween.

According to the above structure for embodying the invention, each of the accommodated filtering membranes can solidly be secured to the corresponding membrane-supporting plate by way of melting both the filtering membranes and the corresponding membrane-supporting plate or either of them via a thermal fusion or irradiation of ultrasonic waves.

To embody a better structure of the filtration membrane cartridge according to the invention, each filtering membrane is bonded to the corresponding membrane-supporting plate via a fusing process applied onto the main fusible domain which is peripherally and linearly formed along periphery of the filtering membrane and subordinate fusible domains which are intermittently formed in plural locations along one side or both sides of the main fusible domains.

According to the above-referred structure for embodying the invention, substantial bonding strength between the filtering membrane and the corresponding membrane-supporting plate is secured by the main fusible domain. Furthermore, bonding strength is reinforced by effect of local fusion applied onto plural subordinate fusible domains.

According to the above-referred better structure of the filtration membrane cartridge for embodying the invention, the membrane supporting plate has a channel for permeated liquid which are

open to the surface of the membrane-supporting plate that faces the corresponding filtering membrane.

According to the above-referred structure for embodying the invention, even when the filtering membrane is closely pressed against the corresponding membrane-supporting plate by effect of negative pressure caused by liquid sucking operation, permeated liquid can securely flow through a plurality of channels constantly open to the surface of the membrane-supporting plate to enable liquid permeated to swiftly flow through the filtration system.

According to the above-referred better structure of the filtration membrane cartridge for embodying the invention, a pair of spacers are inserted between the filtering membranes and the corresponding membrane-supporting plate.

According to the above-referred structure for embodying the invention, in resistance against negative pressure, each spacer supports the corresponding filtering membrane by providing predetermined space on the corresponding membrane-supporting plate to enable liquid filtered out of the filtering membrane to swiftly flow through the predetermined space.

To achieve the above objects, the invention provides an improved filtration-membrane cartridge. Each of a predetermined number of the inventive filtration-membrane cartridges is inserted in the corresponding gutter of a slit plate provided inside of the filtering-membrane unit. In particular, the invention provides a plurality of projections on peripheral edges (being opposite from the inner surface of the gutter of the slit plate) of the filtration membrane cartridge to enable these projections to slide themselves to come into contact with the inner surface of the gutter provided in the slit plate.

According to the above-referred structure for embodying the invention, whenever inserting the filtration membrane cartridge into the corresponding gutter and removing it therefrom, the filtration membrane cartridge is slidably brought into contact with the inner surface of the corresponding gutter of the slit plate by effect of plural projections set to peripheral edges of the filtration membrane cartridge. This in turn contracts contact area of the cartridge against the gutter to reduce frictional force to facilitate operator to easily insert and remove the filtration membrane cartridge into and from the filtering membrane unit.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an overall perspective view of the filtration membrane cartridge according to an embodiment of the invention;

Fig. 2 is a plan designating a structure for retaining the filtration membrane cartridge in position according to an embodiment of the invention;

Fig. 3 is a front view of the filtration membrane cartridge according to an embodiment shown in Fig. 2;

Fig. 4 is a lateral view of the filtration membrane cartridge according to an embodiment shown in Fig. 2;

Fig. 5 is a cross-sectional view of the filtration membrane cartridge across arrowed line A - A shown in Fig. 3;

Fig. 6 is a cross-sectional view of the filtration membrane cartridge across arrowed line B - B shown in Fig. 5;

Fig. 7 is a schematic pattern of the groove formed in the membrane-supporting plate according to an embodiment of the invention;

Fig. 8 is another schematic pattern of the groove formed in the membrane-supporting plate according to another embodiment of the invention; Fig. 9 is a partially enlarged cross-sectional view of the filtration membrane cartridge according to the invention;

Fig. 10 is a cross-sectional view designating another example of the disposition of the filtering membrane against the corresponding membrane-supporting plate;

Fig. 11 is a front view designating another structure of grooves formed in the membrane-supporting plate;

Fig. 12 is a cross-sectional view of the membrane-supporting plate across arrowed line C - C shown in Fig. 11;

Fig. 13 is a cross-sectional view of the membrane-supporting plate across arrowed line D - D shown in Fig. 11;

Fig. 14 is a cross-sectional view of the membrane-supporting plate across arrowed line E - E shown in Fig. 11;

Fig. 15 is explanatory of a method of bonding a filtering membrane to the corresponding membrane-supporting plate;

Fig. 16 is a schematic pattern designating a structure of fused domains in the filtration membrane cartridge according to the invention;

Fig. 17 is a schematic pattern designating another structure of the fused domains in the filtration membrane cartridge according to the invention;

Fig. 18 is a schematic pattern designating another structure of the fused domains in the filtration membrane cartridge according to the invention; and

Fig. 19 is explanatory of another method of bonding a filtering membrane to the corresponding membrane-supporting plate.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the accompanying drawings, full details of the improved filtration membrane cartridge according to an embodiment of the invention are described below. Those essential components having function identical to that of the corresponding components shown in Fig. 1 are designated by identical reference numerals, and thus, description of these is deleted.

Refer now to Figures 2 through 9, in which a plurality of filtration membrane cartridges 5 are retained by a plurality of corresponding slit plates 11 which are accommodated in an upper casing 4 of a filtration membrane assembly unit 3. More particularly, as shown in Fig. 1, a plurality of gutter 12 are formed in each slit plate 11 at predetermined intervals. A plurality of filtration membrane cartridges 5 are vertically inserted in the corresponding gutter 12 in parallel with each other.

Each of the filtration membrane cartridges 5 has a novel structure comprising a pair of filtering membranes 52 each consisting of an organic membrane such as an ultrafiltration membrane or microfiltration membrane, which are disposed on both surfaces of the plane rectangular membrane-supporting plate 51 made from resin such as PVC for example. A pair of filtering membranes 52 are peripherally secured to the corresponding membrane-supporting plate 51 by applying a fusing process.

Although the present embodiment has disposed the filtering membranes 52 on both surfaces of the corresponding membrane-supporting plate 51, alternatively, as shown in Fig. 10, a single sack-like filtering membrane 52 may also be disposed by way of fully covering the membrane-supporting plate 51. The novel method of bonding the filtering membranes 52 to the corresponding membrane-supporting plate 51 will be described later on.

A channel for permeated liquid further inside of the filtering membranes 52 is linked with a branch tube 9 routed from a suction tube 8 for sucking permeated liquid at one side of the membrane-supporting plate 51 in the filtration membrane cartridge 5. Raw liquid is filtered by these filtration membrane cartridges 5 by effect of negative pressure generated by a suction pump 10 via a liquid suction tube 8.

A plurality of projections 53 are disposed on peripheral edges of the membrane-supporting plate 51 at predetermined intervals, more particularly, on a pair of parallel sides opposite from respective gutter 12 of respective slit plates 11. Those plural filtration membrane cartridges 5 are secured to the filtering-membrane unit 3 by slidably bringing those projections 53 into contact with inner surface of the

corresponding gutter 12.

Each of these projections 53 is elliptically shaped in the vertical direction of the filtration membrane cartridge 5. For example, in order to manufacture the filtration membrane cartridges 5 having 1000mm of length and 500mm of width, the filtration membrane cartridge 5 is essentially provided with a number of projections 53 each having 5mm of long diameter, 1 to 2mm of short diameter, and 0.5mm of height, by a certain number ranging from 6 to 20 units per surface of the filtration membrane cartridge 5.

Since those projections 53 and the inner surface of the gutter 12 come into contact with each other via confined contactable area to cause minimal friction to occur, operator can readily insert and take out each filtration membrane cartridge 5 into and from the corresponding gutter 12 of the slit plate 11.

Even though distortion ever occurs in the filtration membrane cartridge 5 or in the slit plate 11, or if the filtration membrane cartridge 5 could not easily be inserted or drawn out as a result of inadequate width of the corresponding gutter 12 provided in the slit plate 11, the filtration membrane cartridge 5 can properly fit in with the gutter 12 merely by scraping off those projections 53.

The membrane-supporting plate 51 of the filtration membrane cartridge 5 incorporates a channel 54 for permeated liquid flowing out of the filtering membranes 52. The channel 54 comprises fine meshy grooves 54a or a plurality of slits 54b or grooves 54a and slits 54b by way of combining them. To implement the present embodiment, the fine meshy grooves 54a are combined with the slits 54b for example. This method is described below.

The fine meshy grooves 54a are formed on both-side surfaces of the membrane-supporting plate 51. Structurally, a plurality of fine linear grooves 54a are linked with each other in mesh form. These grooves 54a are formed by applying an etching process against a metal mold used for molding the membrane-supporting plate 51. These fine linear grooves 54a are linked with peripheral edges of apertures of the slits 54b. As shown in Figures 7 and 8, these fine linear grooves 54a may be disposed in parallel with or at an oblique angle against the horizontal and vertical sides of the rectangular membrane-supporting plate 51. Although the present embodiment uses the fine meshy grooves 54a, when being combined with the slits 54b, these fine meshy grooves 54a may be arranged in striped pattern. Each of these fine meshy grooves 54a has less than 1mm of depth, less than 1mm of width, and less than 5mm of intervals between adjoining grooves 54a. On the other hand, those slits 54b each having an appropriate depth are respectively open to the surface of

the membrane-supporting plate 51 and disposed in parallel with vertical sides of the membrane-supporting plate 51. As shown in Figures 11 through 14, those slits 54b may be formed by way of extending themselves in the direction of the thickness of the membrane-supporting plate 51. A sump of permeated liquid 55 is formed at a location close to an end and along widthwise direction of the membrane-supporting plate 51. The sump 55 is linked with the fine meshy grooves 54a and the slits 54b at peripheral edges of apertures on the surface of the membrane-supporting plate 51. A suction port 56 is formed at the upper end of the membrane-supporting plate 51 so that it can be linked with the sump 55. The branch tube 9 routed from the suction tube 8 is connected to the suction port 56.

When activating the suction pump 10 to apply negative pressure to the filtration membrane cartridge 5 via the suction tube 8, permeated liquid is sucked into the filtration membrane cartridge 5, and then permeated liquid out of the filtering membranes 52 flows into the sump 55 via those fine meshy grooves 54a and those slits 54b formed inside of the membrane supporting plate 51 to flow into the branch tube 9 of the suction tube 8 from the suction port 56.

While the above processes are underway, even though the filtering membranes 52 closely adhere to the membrane-supporting plate 51 by effect of negative pressure, since flow of permeated liquid on the surface of the membrane-supporting plate 51 can be secured by means of the fine meshy grooves 54a and the slits 54b, permeated liquid can easily flow through space between the filtering membranes 52 and the membrane-supporting plate 51. Especially, where slits 54b are formed, the distance of the flow of permeated liquid in the fine meshy grooves 54a shortens, facilitating smoother flow of the liquid.

A pair of spacers 57 are provided between the membrane-supporting plate 51 and the filtering membranes 52. Each of these spacers 57 provides predetermined interspace between the membrane-supporting plate 51 and the filtering membranes 52 to facilitate permeated liquid to smoothly flow therethrough. Each of these spacers 57 is composed of a felt-like sheet or a plastic net or a metallic net. Each of the filtering membranes 52 has configuration greater than that of the spacer 57 enough to fully cover the spacer 57, and therefore, these spacers 57 are prevented from coming into direct contact with the raw liquid.

According to the structure described above, since the spacers 57 respectively support the filtering membranes 52 by way of resisting negative pressure caused by permeated liquid suction operation by means of predetermined space formed

on the membrane-supporting plate 51, and therefore, permeated liquid out of the filtering membranes 52 can swiftly flow through the predetermined space. When implementing the present embodiment, these spacers 57 are provided in conjunction with permeated liquid channels 54. However, it is also practicable for the embodiment to solely provide these spacers 57 by way of deleting the permeated liquid channels 54.

Next, the method of fusibly bonding the filtering membranes 52 to the membrane-supporting plate 51 is described below. As shown in Fig. 15, the membrane-supporting plate 51, the filtering membranes 52, and the spacers 57, are superposed in sequence. In the present embodiment, the filtering membranes 52 comprises a thermoplastic non-woven cloth 52a made from saturated polyester resin functioning as the supporting body and a membrane as a surface layer 52b integrated with each other. However, the filtering membrane 52 may be of the one devoid of the non-woven cloth 52a. Those spacers 57 are not always essential for embodying the filtration membrane cartridge related to the invention.

After superposing those components mentioned above, a horn 13 is set to a predetermined position above the filtering membranes 52 in order to oscillate ultrasonic wave. Either a rotary horn 13 or a stationary horn 13 is usable, where the rotary horn 13 is specifically used when processing compactly composed filtering membranes 52. On the way of moving over the filtering membranes 52, the horn 13 oscillates ultrasonic wave to fusibly bond the filtering membranes 52 to the membrane-supporting plate 51.

As mentioned above, since the non-woven cloth 52a functioning as the substrate for supporting the filtering membranes 52 is made from saturated polyester resin, the non-woven cloth 52a is subject to melting at a temperature above 140° C. for example. On the other hand, the membrane-supporting plate 51 is subject to melting at a temperature lower than the melting point of the non-woven cloth 52a in that the membrane-supporting plate 51 is made from ABS resin or the like. Therefore, when applying temperature lower than about 140° C., the membrane-supporting plate is melted to cause the molten resinous component to infiltrate into the non-woven cloth 52a, thus causing the filtering membranes 52 to be bonded to the membrane-supporting plate 51.

On exposure to temperature higher than about 140° C., both the membrane-supporting plate 51 and the non-woven cloth 52a are subject to fusion with each other.

Even when thermally treating the filtering membranes 52 devoid of the non-woven cloth 52a, the filtering membranes 52 can securely be fused with

the membrane-supporting plate 51 by means of molten resinous component of the membrane-supporting plate 51 or by effect of the simultaneous fusion of the resinous component of the membrane-supporting plate 51 and the filtering membranes 52.

On the way of executing the thermal fusion process by applying ultrasonic wave, objective resinous component is apt to melt from the inner domain, and thus, it is desired that the horn 13 be activated via a thermally resistant tape disposed on the filtering membranes 52. Instead of the above fusing method using ultrasonic wave, local thermal treatment can also be performed for locally fusing the filtering membranes 52 with the membrane-supporting plate 51.

As described above, the filtering membranes 52 can solidly be bonded to the membrane-supporting plate 51 by causing the plastic membrane-supporting plate 51 and the filtering membranes 52 incorporating plastic substrate or either of these to be fused with each other via a thermal treatment or irradiation of ultrasonic wave.

As shown in Figures 16 and 17, the membrane-supporting plate 51 and the filtering membranes 52 are fused with each other via the main fusible domain 14a peripherally and linearly provided along peripheral edges of the filtering membranes and the subordinate fusible domains 14b intermittently provided on a single side or on both sides of the main fusible domain 14a.

The main fusible domain 14a is provided in order to secure water-sealing effect and fundamental bonding strength. On the other hand, the subordinate fusible domains 14b are intermittently provided in plural positions in order to prevent the filtering membranes 52 from being wrinkled, and yet, the subordinate fusible domains 14b respectively reinforce the bonding strength between the membrane-supporting plate 51 and the filtering membranes, 52. Considering economy of thermal energy and better effect of fusion, it is desired that the main fusible domain 14a be formed with narrow width. By effect of providing the subordinate fusible domains 14b on the outer side of the main fusible domain 14a, unfused portion of the filtering membranes 52 is protected so that the filtering membranes 52 can fully be prevented from being stripped off from the membrane-supporting plate 51. Nevertheless, in the event that there is no fear of causing the filtering membranes 52 to be stripped off along the peripheral edges, it is possible for the embodiment to confine provision of the subordinate fusible domains 14b solely to the central part of the filtering membranes 52. As shown in Fig. 18, not only the intermittent and linear formation, but the subordinate fusible domains 14b may also be provided in a variety of patterns such as

the one being disposed at predetermined intervals for example.

As shown in Fig. 19 for example, prior to the execution of a fusion process between the membrane-supporting plate 51 and the filtering membranes 52, a plurality of projected fusible domains 51a may integrally be formed on the membrane-supporting plate 51. When implementing this method, initially, each of the filtering membranes 52 is disposed by way of fully concealing the projected fusible domains 51a, and then, the fusible domains 51a are melted via a thermal treatment or irradiation of ultra-sonic wave before executing a compressive fusing process to fuse the membrane-supporting plate 51 with the filtering membranes 52 at locally melted regions.

As a result of the provision of the above structure, the filtering membranes 52 can securely be bonded to the membrane-supporting plate 51 by way of preventing the main component of the membrane-supporting plate 51 from being melted, and yet, by way of preventing deformation in the periphery of melted regions and subsequent deformation of the filtering membranes 52 from occurrence. The above projected fusible domains 51a may also be formed using members having any shape other than that of the membrane-supporting plate 51, like bar-shaped members for example.

Claims

1. A filtration membrane cartridge comprising;
a plurality of filtering membranes disposed on both surfaces of a resin membrane-supporting plate; wherein said filtering membranes are individually fused with said membrane-supporting plate at edges of said filtering membranes.
2. The filtration membrane cartridge as defined in Claim 1, wherein each of said filtering membranes is bonded to said membrane-supporting plate at a main bondable domain which is peripherally and linearly formed along peripheral edges of each of said filtering membranes and at a plurality of subordinate fusible domains intermittently formed in plural local regions on one side or on both sides of said main fusible domain.
3. The filtration membrane cartridge as defined in Claim 1, wherein said membrane-supporting plate incorporates a plurality of channels for permeated liquid respectively being open to surface of said membrane-supporting plate facing said filtering membranes.
4. The filtration membrane cartridge as defined in Claim 1, wherein a plurality of spacers are

respectively interposed between said filtering membranes and said membrane-supporting plate.

5. A filtration membrane cartridge which is disposed by way of being inserted in each gutter of a slit plate provided in a filtration membrane assembly unit wherein comprising;
- a plurality of projections formed on peripheral edges of each filtration membrane cartridge facing inner surface of each gutter formed inside of slit plate, wherein said projections respectively come into contact with said inner surface of said gutter by way of sliding themselves.

5

10

15

20

25

30

35

40

45

50

55

FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11

FIG.12




FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG.18





FIG.19





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 93 11 9930

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL.5)
Y	EP-A-0 457 676 (EURODIA S.A.) * claims; figures * ---	1-5	B01D63/08 B01D69/10 B01D65/00
Y	DE-A-37 28 825 (FUJI PHOTO FILM CO) * claims; figures 2,5-7 * ---	1-5	
Y	FR-A-2 478 483 (MILLIPORE CORPORATION) * figure 10 * ---	1-5	
A	DE-A-23 03 860 (RHONE-POULENC) * claims; figures 3,4 * ---	1-5	
A	DE-A-37 26 865 (FUJI PHOTO FILM CO) * claims; figures 2,3,5,7,8 * -----	1-5	
			TECHNICAL FIELDS SEARCHED (Int. CL.5)
			B01D
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 18 April 1994	Examiner Cordero Alvarez, M
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			